



GATOR CLEAN EFFLORESCENCE & SLURRY REMOVER FOR CONCRETE PAVER & NATURAL STONES

TDS Revision Date (dd/mm/yyyy): 03/02/2026



TECHNICAL DATA SHEET

Update:

February 3, 2026

Make sure you have an updated data sheet on hand.

Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

Description:

GATOR EFFLORESCENCE & SLURRY REMOVER will remove any efflorescence stains trapped in the concrete pavers, wetcast & natural stone pores. It will make the pavers look more clean and vibrant without discoloring or damaging the paver surface. This efflorescence cleaning is a necessary step before a sealer is applied. The sealer will be able to get a deeper penetration into the now clean pores.

Features:

- Removes efflorescence from the surface of concrete pavers, wetcast & natural stones.
- Slurry remover.
- Washes off with water.

For use on:

Concrete Pavers, Wetcast, Natural Stones and Slurry.

Coverage:

- 5 US gal. (18,9 L) of **GATOR EFFLORESCENCE & SLURRY REMOVER** diluted with 40 US gal (151,2 L) of water, cleans approx 1800 sq.ft (167,3 sq. m.) or 40 sq.ft. (3,72 sq.m.) per US gallon (3,78L).

Please note:

1. **GATOR EFFLORESCENCE CLEANER & SLURRY REMOVER** should be used prior to applying a sealer to ensure a proper sealer adhesion.
2. Freshly installed [Flexlock Polymeric Sand](#) must be allowed to cure for 48 hours at above 59°F (15°C) and no rain before using **GATOR EFFLORESCENCE CLEANER & SLURRY REMOVER**.
3. Do not let product dry up on paver surface.
4. Wear goggles and rubber gloves.
5. Never use on new concrete pavers. Wait at least 60 days after new pavers are installed before using this product.
6. ALWAYS TEST the product on a small hidden area of approximately 4 sq. ft. (0.4 sq. m.) to ensure the results will meet your expectations. Do not apply under extremely strong sun.
7. Dilute to 8 parts water, 1 part **GATOR EFFLORESCENCE CLEANER & SLURRY REMOVER** concentrated liquid, any concentration greater than this can discolor the pavers.

Ideal mixture:

8 parts water 1 part **GATOR EFFLORESCENCE & SLURRY REMOVER**. Always test the ideal mixture on a small inconspicuous area of 0.4 sq. m.(4 sq. ft.) to insure no etching. Further dilution is possible. You must test all dilutions on small inconspicuous areas of 0.4 sq. m. (4 sq. ft.) to insure that there is no etching.



GATOR CLEAN EFFLORESCENCE & SLURRY REMOVER FOR CONCRETE PAVER & NATURAL STONES

TDS Revision Date (dd/mm/yyyy): 03/02/2026



Application instructions:



1. Wet paver surface with water.
2. Use a pump sprayer or watering can to apply the diluted product on the wet paver surface. Wait one minute for product to react then scrub the surface vigorously using a hard bristle brush. 1 U.S. gal. (3.78 L.) of diluted **GATOR EFFLORESCENCE & SLURRY REMOVER** is to be used for every 40 sq. ft. (3,72 sq. m.) of paver surface.
3. Rinse thoroughly with water and move on to the next section of 40 sq. ft. (3,72 sq. m.).
4. Repeat steps 2 & 3 over all the sections in question.
5. Once the surface is clean, use water hose and generously rinse off **GATOR EFFLORESCENCE CLEANER & SLURRY REMOVER** until there is no more foaming action on the pavers.

NOTE: You might have to redo it again if there is a lot of efflorescence trapped in the pavers.

Packaging:	Product	Pail size	Per pallet
	Gator Efflorescence & Slurry Remover	18.9 L (5 U.S. gal.)	48 pails

LIMITED WARRANTY:

Before applying the product, the user/buyer must determine its suitability for intended use and user/buyer assumes all risks in that regard. It is a condition of the Limited Warranty that before using the product on the intended larger area, the user/buyer must first test the product on a small less observed area of approximately 4 sq. ft. (0.4 sq. m.) to ensure results meet user/buyer's expectations. In the event that no test is carried out, the Limited Warranty will only apply to 4 sq. ft. (0.4 sq. m.). ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation ALLIANCE DESIGNER PRODUCTS INC. is to refund the purchase price. Proof of purchase is required for any claim. ALLIANCE DESIGNER PRODUCTS INC. shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, ALLIANCE DESIGNER PRODUCTS INC. excludes any implied warranty of quality, merchantability or fitness for purpose.

The container must at all times be stored at above 0°C / 32°F to receive the benefit under the Limited Warranty.