



**GATOR SATIN LOOK**  
**FOR DRY CAST CONCRETE PAVERS**  
TDS Revision Date (dd/mm/yyyy): 28/05/2026



# TECHNICAL DATA SHEET

- Update:** May 28, 2026  
Make sure you have an updated data sheet on hand.  
Canada and U.S. dial **1-855-847-7767** or (450) 624-1611
- Description:** **GATOR SEAL SATIN LOOK SEALER** is made from acrylic-based polymers. **GATOR SEAL SATIN LOOK SEALER** penetrates deep into the concrete pavers, therefore helps prevent oil and dirt stains, the damage caused by from de-icing salt and the effects of the UV rays. Specifically formulated to be used on unsealed surfaces only.
- Features:**
- Easier to clean and maintain
  - Solvent-based
  - Film Former
  - Low-gloss & color enhancer finish
  - Joint stabilizer
  - Helps prevent oil and dirt stains, damage from de-icing salt and effects from the UV rays
- Coverage:** • 1 u.s. gal. (3.78 l) covers 175 ft<sup>2</sup> (16 m<sup>2</sup>)
- For use on:** For dry cast concrete pavers
- Please note:**
- Concrete pavers should only be sealed 60 days after their installation date. Consult concrete paver manufacturer's for their recommendation.
  - Concrete pavers and jointing sand **MUST** be 100% dry.
  - Temperature should be between 60°F (16°C) and 85°F (29°C) when sealer is applied.
  - Concrete paver surface must be cool to the touch when sealer is applied (between 60°F (16°C) and 85°F (29°C)).
  - First clean concrete pavers with [Gator Clean products](#). Remove all oil, grease and rust stains.
  - Use [Gator Efflorescence Cleaner](#) to remove any trapped efflorescence. It also thoroughly cleans the surface to ensure a proper sealer adhesion.
  - Apply only one (1) coat.
  - Ensure that the surface has been exposed to dry conditions for 48 hours before applying **GATOR SEAL SATIN LOOK**. Note: If the temperature is above 60°F (16°C), the surface should dry within hours.
  - Specifically formulated to be used on unsealed surfaces only. Cannot be used as a resealer.
  - Wear protective gloves, eye protection and respiratory protection.



**GATOR SATIN LOOK  
FOR DRY CAST CONCRETE PAVERS**

TDS Revision Date (dd/mm/yyyy): 28/05/2026



**Application instructions:**



1. ALWAYS TEST the product on a small hidden area of approximately 4 sq. ft. (0.4 sq. m.) to ensure the results will meet your expectations.
2. Remove all the stains from the concrete pavers, using [Gator Clean products](#). Use [Gator Clean Sealer Stripper](#) to remove any unknown coating that remains on the concrete paver surface.
3. Remove all contaminated jointing material and replace with [Flexlock Polymeric Sand](#). Follow the instructions on the back of the bags for proper sand installation.
4. Wait at least 48 hours at a minimum temperature of 60°F (16°C) and no rain for the [Flexlock Polymeric Sand](#) to properly harden.
5. Clean the entire surface with the [Gator Efflorescence Cleaner](#). This product will remove the efflorescence trapped in the concrete paver pores as well as thoroughly clean the surface for proper sealer adhesion.
6. Wait at least 48 hours at a minimum temperature of 60°F (16°C) with no rain, to make sure that the sand and concrete paver surfaces are dry.
7. Best Practice: ([See online video. 2 people needed.](#)) Apply one (1) coat of **GATOR SEAL SATIN LOOK SEALER** using a sprayer in 60 sq. ft (5.6 sq. m.) sections, then use a solvent-resistant foam roller to remove the excess sealer left on the surface.
8. **GATOR SEAL SATIN LOOK** creates a water-repellent and rain-safe surface after 90 min.
9. Let the sealer dry for 24 hours before using the sealed area.

**Coating Category:** Low Solids Coatings. VOC Concentration Limits: <120 g/L (grams of VOC per liter of material).

Packaging:	Product	Size	per Box	per Pallet
	<b>GATOR SEAL SATIN LOOK SEALER</b>	3.78 L (1 U.S. gal.)	4 units	24 boxes
	<b>GATOR SEAL SATIN LOOK SEALER</b>	18.9 L (5 U.S. gal.)		48 pails

**LIMITED WARRANTY:**

Before applying the product, the user/buyer must determine its suitability for intended use and user/buyer assumes all risks in that regard. It is a condition of the Limited Warranty that before using the product on the intended larger area, the user/buyer must first test the product on a small less observed area of approximately 0.4 sq. m. (4 sq. ft.) to ensure results meet user/buyer's expectations. In the event that no test is carried out, the Limited Warranty will only apply to 0.4 sq. m. (4 sq. ft.). ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation ALLIANCE DESIGNER PRODUCTS INC. is to refund the purchase price. Proof of purchase is required for any claim. ALLIANCE DESIGNER PRODUCTS INC. shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, ALLIANCE DESIGNER PRODUCTS INC. excludes any implied warranty of quality, merchantability or fitness for purpose. The container must at all times be stored at above 0°C and away from direct sun to receive the benefit under the Limited Warranty.

This sealer is to be employed without thinning or diluting under normal environmental conditions. Use acetone for cleaning. Alliance Designer Products shall not be liable for any non-compliant use.



**Flexlock**  
 1800 Berlier st. suite 200, Laval, Quebec, Canada H7L 4S4  
 Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611  
 www.flex-lock.com - E-mail : info@flex-lock.com